





## Main

Range of product	TeSys F
Product or component type	Contactors
Device short name	LC1F
Contactors application	Motor control Resistive load
Utilisation category	AC-1 AC-3
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	<= 460 V DC <= 1000 V AC 50/60 Hz
[Ie] rated operational current	800 A (<= 55 °C) at <= 440 V AC AC-3 1000 A (<= 40 °C) at <= 440 V AC AC-1
Motor power kW	250 kW at 220...240 V AC 50/60 Hz 475 kW at 660...690 V AC 50/60 Hz 450 kW at 500 V AC 50/60 Hz 450 kW at 440 V AC 50/60 Hz 450 kW at 415 V AC 50/60 Hz 450 kW at 380...400 V AC 50/60 Hz 450 kW at 1000 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
Overvoltage category	III
[Ith] conventional free air thermal current	1000 A at <= 40 °C
Irms rated making capacity	8000 A AC conforming to IEC 60947-4-1
Rated breaking capacity	6400 kA conforming to IEC 60947-4-1
[Icw] rated short-time withstand current	2200 A <= 40 °C 10 min 3000 A <= 40 °C 3 min 4600 A <= 40 °C 1 min 5600 A <= 40 °C 30 s 6250 A <= 40 °C 10 s
Associated fuse rating	800 A aM at <= 440 V
Average impedance	0.12 mOhm at 50 Hz - Ith 1000 A
[Ui] rated insulation voltage	1500 V conforming to VDE 0110 group C 1000 V conforming to IEC 60947-4-1
Power dissipation per pole	77 W AC-3 120 W AC-1
Mounting support	Plate
Standards	EN 60947-1 EN 60947-4-1 IEC 60947-1 IEC 60947-4-1 JEM 1038
Product certifications	CSA GL UL LROS

Connections - terminals	Power circuit: bar 2 x ( 60 x 5 mm) Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 1 cable(s) 1...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end
Tightening torque	Power circuit: 58 N.m Control circuit: 1.2 N.m

## Environment

IP degree of protection	IP20 front face with shrouds (ordered separately) conforming to VDE 0106 IP20 front face with shrouds (ordered separately) conforming to IEC 60529
Protective treatment	TH
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Permissible ambient air temperature around the device	-5...55 °C
Operating altitude	3000 m without derating in temperature
Mechanical robustness	Vibrations contactor closed 4 Gn, 5...300 Hz Shocks contactor open 6 Gn for 11 ms Shocks contactor closed 15 Gn for 11 ms Vibrations contactor open 2 Gn, 5...300 Hz
Height	304 mm
Width	309 mm
Depth	255 mm
Product weight	18.75 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0843 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Available

## Contractual warranty

Period	18 months
--------	-----------